




fiorentini

we clean the world

ECOSMILE



caratteristiche tecniche	technical specification	caractéristiques techniques		ecosmile 65	ecosmile 75	ecosmile 85	ecosmile 70R	ecosmile 100
larghezza utile lavoro	scrubbing width	largeur de nettoyage	mm	650	750	850	700	960
rendimento orario max	cleaning capacity up to	rendement jusqu'à	mq/h	4000	4500	5000	4200	5750
autonomia	operating range	autonomie	h	5	5	5	4	5
capacità serbatoio soluzione	solution tank capacity	capacité réservoir solution	L	150	150	150	150	150
capacità serbatoio recupero	recovery tank capacity	capacité réservoir récupération	L	150	150	150	150	150
trazione	traction method	tracion		Anteriore - Motoruota / Front - Drive wheel / Roue motrice avant				
velocità di avanzamento	forward speed	vitesse d'avancement	km/h	0-6	0-6	0-6	0-6	0-6
max pendenza	max. slope	pente max. surmontable	%	10	10	10	10	10
depressione	water lift	dépression	mBr	170	170	170	170	170
pressione testata spazzole	brush pressure	pression des brosses	kg	41	46	51	48	55
rumorosità	noise level	bruit	dB	72	72	72	72	72
corridoio di sterzata	width for u-turn	couloir pour demi-tour	mm	1720	1720	1720	1720	1800
alimentazione	voltage	alimentation		ecosmile 65	ecosmile 75	ecosmile 85	ecosmile 70R	ecosmile 100
motore aspirazione	vacuum motor	moteur d'aspiration		750w	750w	750w	750w	750w
motore spazzola	brush motor	moteur des brosses		2 x 400w	2 x 400w	2 x 400w	2x600	2x400
motore trazione	traction motor	moteur traction		500w	500w	500w	500w	500w
alimentazione	voltage	alimentation		48vdc	48vdc	48vdc	48vdc	48vdc
Batterie	Batteries	Batteries		4x12vx157A	4x12vx157A	4x12vx157A	4x12vx157A	4x12vx157A
dimensioni	dimensions	dimensions		ecosmile 65	ecosmile 75	ecosmile 85	ecosmile 70R	ecosmile 100
dimensioni	dimensions	dimensions		1350x710x1360	1350x820x1360	1350x820x1360	1350x820x1360	1350x820x1360
diametro spazzole	brush diameter	diamètre de la brosse	mm	2xØ330mm	2xØ380mm	2xØ410mm	2xØ650mm	2xØ480mm
larghezza tergipavimento	squeegee width	largeur du suceur	mm	920	1020	1120	1020	1240
peso macchina	weight of the machine	poids de la machine	kg	170	170	170	170	170
peso batterie	weight of the batteries	poids des batteries	kg	4x37	4x37	4x37	4x37	4x37



stabilimenti produttivi

50033 Piancaldoli (FI) via Piancaldoli 1896 Firenzuola
tel +39 0558173610 - fax +39 055817144

50033 Pietramala (FI) via pietramala 70/B
tel +39 055813447 - fax +39 055813504

40024 Castel San Pietro (BO) via Cà Bianca 231/C
tel +39 051941743 - fax +39 0516942400

filiali commerciali

20132 Milano via Palmanova 211/A
tel +39 0227207783 - fax +39 022592779

00012 Guidonia Montecelio (Roma) via Bruno Pontecorvo 20
tel +39 0774357184 - fax +39 0774353419

dati aziendali

ing. O. Fiorentini s.p.a. via Piancaldoli, 1896 - Firenzuola
50033 Fraz. Piancaldoli (FI) - Italia

P.I. 06113160482

Certificazione ISO 9001:2015

e-Mail: info@ingfiorentini.it